




**1. Portable Digital Inclinometer (N)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>04</b>
2.	Material	Zinc Alloy or Aluminum	
3.	Size	To be indicated by supplier	
4.	Manufacturing standard	To be indicated by supplier	
5.	Power	Battery	
6.	Other Specifications	<p>Item should consist with all relevant accessories. Strong durability and long service life.</p> <p>Item should contain with a large LCD display for easy reading of measured data.</p> <p>Item should be provide data hold function for Angle and slope readout.</p> <p>It should be Built-in magnet in bottom surface which convenient to be attached to the work piece for easy measurement.</p>	


**2. Load Bearing Harness And Belt (N)**

Sr No	Specifications	Descriptions	Quantity
<b>01</b>	Picture		<b>04</b>
2.	Color	To be indicated by supplier	
3.	Manufacturing standard	To be indicated by supplier	
4.	Size	Universal	
5.	Material	1000D -Cordura or waterproof equivalent fabric	
6.	Other Specifications	<p>Item should consist with all relevant accessories.</p> <p>Ex;- load bearing cross belt, harness covered pockets, radio pockets, back pack, waterproof zippers, Fog Manual pockets, mobile attachment system, detachable belt and spring clips to hang glow stick.</p>	


**3. USAR Search Markings Kit (N)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
2.	Tape Color	Red or Yellow	
3.	Manufacturing standard	To be indicated by supplier	
4.	Other Specifications	Item should consist with all relevant accessories Ex;- marking paint, marking pen and chalk Item should provide with water proof zippered pouch containing extra pockets.	


**4. Safety Cones (N)**

Sr No	Specifications	Descriptions	Quantity
	<b>Safety Cones</b>		<b>04</b>
2.	Length	20 - 50 In	
3.	Width	10 - 20 In	
4.	Colour	Orange or equivalent	
5.	Visibility	Hi-Visibility	
6.	Weight	1.5 - 5 Kg	
7.	Material	Molded PVC or equivalent	
8.	Other Specifications	Item should contain wide body Injection molded PVC which assures durability and flexibility in all weather conditions. Item should long lasting, light weight and simple installation features with brilliant fluorescent color provides. It should include high density base to maintain low center of gravity for maximum stability. It should be Hi-intensity reflective collars/tapes to provide maximum visibility with design for easy storage and movability.	


**5. Knee Guard (N)**

<b>Sr No</b>	<b>Specifications</b>	<b>Descriptions</b>	<b>Quantity</b>
1.	Picture		<b>08</b>
2.	Color	To be indicated by supplier	
3.	Material	Neoprene and Foam padding	
4.	Other Specifications	Item should consist with all relevant accessories. hard shell, adjustable rubber straps Item should provide support for kneeling and crawling. Should provide strength and abrasion resistance	


**6. Whistle (N)**

<b>Sr No</b>	<b>Specifications</b>	<b>Descriptions</b>	<b>Quantity</b>
1.	Picture		<b>40</b>
2.	Color	To be indicated by supplier	
3.	Material	Stainless steel or equivalent	
4.	Size	To be indicated by supplier	
5.	Other Specifications	Item should be effective and reliable for personal safety and rescue professionals. Item should emits shrill piercing sound which is louder and clearer than ordinary whistles. Item required contain a key ring and should possess portable, durable, wear resistant and lightweight features. Should facilitate for long-distance communication in the field and to send a signal to survive	

**7. Ear Protectors (N)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>08</b>
2.	Color	To be indicated by supplier	
3.	Manufacturing standard	To be indicated by supplier	
4.	Weight	250 – 400g	
5.	Noise reduction rates	20- 30 dB	
6.	Style	Over the head	
7.	Other Specifications	Item should consisted with all relevant accessories. Ex-; Foldable headband. Light weight and comfortable features.	
8.	Material	Plastic – Stainless steel or Equivalent	


**1. Eye Protector (N)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>03</b>
2.	Color	Transparent	
3.	Manufacturing standard	To be indicated by supplier	
4.	Make	Goggle type	
5.	Material	Polycarbonate lens , PVC frame and elastic band	
6.	Other Specifications	Item should provide with all relevant accessories. Should able to use with N95 respirator Facilitate to avoid nanoparticles and strap should adjustable	


**1. Goggles (Amv)**

Item	Description	Quantity
		<b>20</b>

**2. Eye Protector (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>20</b>
2.	Product type	prescription safety spectacles	
3.	Frame type	full-view	
4.	Standards	EN 166	
5.	Material	plastic	
6.	Colour	anthracite, lime	
7.	Frame eye size	61 mm	
8.	Bridge width	14 mm	

**1. Heavy-duty Gloves (Amy)**


Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>20</b>
2.		mechanical protection, cut protection, thermal risks	
3.	Product family	uvex NK	
4.	Version	approx. 40 cm, with gauntlet	
5.	Coating	nitrile rubber (NBR special)	
6.	Coated area	entire glove	
7.	Norm	EN 388:2003, EN 407	
8.	Standards	EN 388:2003 (3 2 4 3), EN 407 (X 1 X X X X)	
9.	Food-compatible	no	
10.	Material	Aramid weave, cotton interlock	
11.	Colour	Orange	
12.	Size	Medium	

Safety Items

**1. Knee Guard (Amy)**


Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>20</b>
	Riding Type	Fly Racing Prizm Knee Guard	
	Pad Type	Dirt Jump / Slope style, Downhill, Free ride / Bike Park, Trail	
	Knee/Shin Coverage	Soft Shell	
	Size	Knee/Shin Pads S, M/L, XL	
	Color	Black	
		CE Level 1 certified to EN1621 / 2012 for knee protection	

**2. Oxygen And Accessories (Amy)**


Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
		Casing with vertical layout and handle, and 4 wheels. Overall dimensions: WDH 41.9x36.8x69.9cm. Weight: 26kg Adjustable flow meter.	
	Power requirement	220 to 240V-50Hz, 2.0 amps, 115V-60HZ 230V-60HZ	
	Power consumption	285W, protected by a 2.5A circuit breaker switch (230V)	
	Oxygen delivery	O2 delivery rate: 5 litres per minute (LMP). Maximum	
	Recommended flow percentage	5 LPM. Outlet pressure: 9.7psig (68.6kPa). Oxygen 1-5 LPM equivalent to 93% ±3%.	

Safety Items


**3. Backboard (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
	Material:	High-density polymer	
	Length:	72"	
	Width:	16"	
	Depth:	1.5" (including runners)	
	Capacity:	500 lbs.	
	Weight:	13.6 pounds	


**4. Cervical Collars (All Sizes) (Amy)**

Item	Description	Quantity
		<b>02</b>


**5. Splints (Amy)**

Item	Description	Quantity
		<b>1 sets</b>


**6. Oropharyngeal Airways (All Sizes) (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		03 sets
	Material:	Soft, flexible, non-toxic material	
	Colour	Different	
	Sizes	All Sizes	


**7. Cpr Dummy Infant (Amy)**

Item	Description	Quantity
		1 sets

**8. Dummy (Child) (Amy)**


Item	Description	Quantity
		1 sets

**9. Dummy (Edult) (Amy)**


Sr No	Specifications	Descriptions	Quantity
1.	Picture		1 sets
	Dimensions	14"x7"x23"	
	Weight	7lbs.	
	Warranty	1 year	




**10. Rappelling Rope (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>100 m = 1</b> <b>200 m = 1</b>
		3/8 Utility Rope	
	Materials	100% Polypro Sleeve	
	Materials	100% Nylon Core	
	Working Load	120lbs	
	Tensile Strength:	1200lbs	


**11. Full Body Harness (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>02</b>
	Materials	Nylon, Polyester, Aluminum, steel	
	Ventral Attachment Point	yes	
	Lateral Attachment Point	yes	
	Rear Attachment Point on the waist belt	yes	
	Certification	CE EN 360 OR ABOVE with an AVAO SIT, FALCON, FALCON MOUNTAIN, SEQUOIA SRT seat harness, EAC	

**12. Carrabina (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
	Weight Capacity	310 lb.	
	Material	Aluminum	
		Chest Strap Buckles None	
		Leg Strap Buckles Quick-Connect	
	Hardware Material	Steel and Aluminum	
		Harness Sizing M/L	
	Webbing Materials	Polyester	
	Standards	ANSI Z359.1, CE EN 12841 type B, CE EN 358, CE EN 361, CE EN 813, CSA Z259.1	
		Gate Opening 51/64 in	


**13. Figure Of 8" (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
	Model	NFPA128701 (Black), NFPA128702 (Grey)	
	Material	Aluminum	
	Finish	Hard-coat Anodized	
	Dimensions	6" x 5.25" x 0.5"	
	Weight	6.5 oz (184g)	
	Max. Rope size	≤ 5/8" (16mm)	
	3 Sigma test	32kN (7,194 lbf)	
		NFPA1983 Certified "T" = 13.5kN (3034 lbf) - 9.5mm to 12.5mm	
		FPA1983 Certified "G" = 22kN (4945 lbf) - 11mm to 16mm	

**14. Rappelling Gloves (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
	Glove Material	Leather	
	Model	SKU/ C-PZ-K53	


**15. Descenders (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>01</b>
		unlock the rope and control the descent with the hand on the free end of the rope move more easily on horizontal or inclined terrain, thanks to the button on the handle position himself without having to tie off the device	
	Lowers heavy load	Lowers heavy loads up to 275 kg	
	colors	red and black	
	Min. rope diameter	11,5 mm	
	Max. rope diameter	13 mm	
	Weight	530 g	


**16. Rig**

Item	Description	Quantity
		<b>02</b>


**17. Ascension (Left) (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>02</b>
		Handled rope clamp for rope ascents.	
	Material	Aluminum, Stainless Steel, Plastic, Rubber, Nylon	
	Weight	165g	


**1. Ascension (Right) (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>02</b>
		Handled rope clamp for rope ascents.	
	Material	Aluminum, Stainless Steel, Plastic, Rubber, Nylon	
	Weight	165g	

**1. Rescue Tube (Amy)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>03</b>
		A brand-new, undamaged item in its original packaging (where packaging is applicable). Packaging should be the same as what is found in a retail store, unless the item is handmade or was packaged by the manufacturer in non-retail packaging, such as an unprinted box or plastic bag.	
	Color	Yellow	

**18. Footage (Amv)**

Sr No	Specifications	Descriptions	Quantity
1.	Picture		<b>02</b>
		Attached to the ASCENSION ascender for rope ascents	
		under foot strap is abrasion-resistant and is slightly rigid to make it easier to step into	
		Adjustable elastic keep easily and quickly adjusts length of foot loop	
	Materials	Nylon, steel	
	Weight	65g	

**Other Conditions:-**

- I. Technical brochure in English -To be indicated by supplier
- II. Warranty period -Minimum 02 or 04 years excluding consumable items
- III. Country of origin -To be indicated by supplier
- IV. Manufacturing standards -ISO, DIN or equivalent
- V. Contact details -Address, e-mail and contact number to be indicated by supplier
- VI. Technical Manual -To be provided by supplier
- VII. Item should be provide with the complete accessories